

SYNCO Pex[®]

Price list / EUR

Single pipe Syncopex® PN6/95°C heating, PN10/70°C warm water



Pipeline designed for central heating in max. of 95° C 6 bar; hot or cold water in max. temp. of 70°C 10 bar. Transmission tube PEX-a SDR 11 made of cross-linked polyethylene with Evoh barrier to prevent oxygen from penetrating into the installation. The pipeline is manufactured according to PN EN 15632-1-3 norm.

Outer casing m/m	200	200	200	160	200	160
Outer pipe PEX m/m DZ	125	110	90	90	75	75
Inner diameter m/m DN	102,2	90	73,6	73,6	61,2	61,2
Bending radius [mb]	1,00	0,80	0,80	0,70	0,70	0,60
Maximum length. [mb]	100	100	100	100	100	100
Catalog No.	100200125	100200110	100200090	100160090	100200075	100160075
Net price EURO for 1 meter	100,00	80,00	69,00	63,00	62,00	53,00

Outer casing m/m	140	125	110	90	90
Outer pipe PEX m/m DZ	63	50	40	32	25
Inner diameter m/m DN	51,4	40,8	32,6	26	20
Bending radius [mb]	0,55	0,45	0,35	0,25	0,25
Maximum length. [mb]	100	100	100	100	100
Catalog No.	100140063	100125050	100110040	10090032	100090025
Net price EURO for 1 meter	45,00	33,00	25,00	21,00	18,00

Pipelines are sold in sections consistent with the design, minimum trade unit 1 mb. The maximum coil lengths are given in the tables above. All net prices, plus VAT 23%

Double pipe Syncopex® heating, PN6/95°C



Pipeline designed for central heating in maximum working temperature of 95° C 6 bar; Transmission pipe PEX-a SDR 11 made of polyethylene cross-linked with Evoh barrier to prevent oxygen from penetrating into the installation. The pipeline is manufactured in accordance with PN EN 15632-1-3 norm.

Pipeline construction is based on the Patent 189276 and includes an air space between pipe insulation and enclosure insulation to form an additional thermal barrier. It is sealed with a thermal plug. Such design also provides an exceptional flexibility of the pipeline. Thermal plug for self-assembly in a set with pipeline in amount suitable for sections.



External housing m / m	250	250	200	160	140	140
Outer PE-X pipe m / m DZ	2x75	2x63	2x50	2x40	2x32	2x25
Inner diameter m / m DN	2x65	2x51,4	2x40,8	2x32,6	2x26	2x20,4
Bending radius [mb]	1,2	0,9	0,7	0,6	0,5	0,5
Maximum length [mb]	100	100	100	100	100	100
Catalog No.	200250275	200250263	200200250	200160240	200140232	200140225
Net price in EURO for 1 meter	101,00	90,00	60,00	47,00	37,00	32,00

Pipelines are sold in sections consistent with the design, minimum trade unit 1 mb. The maximum coil lengths are given in the tables above. All net prices, plus VAT 23%

Double pipe Syncopex®, warm water, PN10/70°C



Pipeline designed for hot water and circulation in max. working temp. of 75° C 10 bar; Transmission pipe PEX SDR 11. Pipeline is manufactured in accordance with PN EN 15632-1-3 * norm, in case of projected temp. of 95° C 10 bar we use PEX SDR 7,4

Pipeline construction is based on the Patent 189276 and includes an air space between the pipe insulation and the enclosure insulation to form an additional thermal barrier and is sealed with a thermal plug. Such design also provides exceptional flexibility of the pipeline. The thermal plug for self-assembly in a set with pipeline in amount suitable for sections.

External housing m / m	250	250	250	200	200	160
PE-X pipe external m / m DZ	1x90	1x75	1x75	1x63	1x63	1x50
	1x50	1x50	1x40	1x40	1x32	1x25
Internal diameter m / m DN	1x73,6	1x65	1x65	1x51,4	1x51,4	1x40,8
	1x40,8	1x40,8	1x32,6	1x32,6	1x26	1x20,4
Bending radius [mb]	1,3	1,2	0,9	0,8	0,8	0,8
Maximum length [mb]	100	100	100	100	100	100
Catalog No.	202509050	202507550	202507540	202006340	202006332	201605025
Net price EUR per 1 meter	116,00	86,00	82	66,00	59,00	43,00

Outer casing m/m	140	140	140	140
Outer pipe PEX m/m DZ	1x40	1x32	1x25	1x20
	1x25	1x20	1x20	1x16
Inner diameter m/m DN	1x32,6	1x26	1x20	1x16
	1x20,4	1x16	1x16	1x12
Bending radius [mb]	0,60	0,50	0,50	0,50
Maximum length. [mb]	100	100	100	100
Catalog No.	201404025	201403220	201402520	201402016
Net price EUR per 1 meter	38,00	34,00	32,00	30,00

Pipelines are sold in sections consistent with the design, minimum trade unit 1 mb. The maximum coil lengths are given in the tables above. All net prices, plus VAT 23%



Quattro pipe Syncopex®, heating PN6/95°C, warm water, PN10/70°C

Pipeline designed for central heating and domestic hot water and circulation in max. working temperature of 95° C 6 bar; 70° C 10 bar. Transmission tube made of polyethylene PEX-a SDR 11 cross-linked with barrier Evoh to prevent oxygen penetration to the installation. Pipeline is manufactured in accordance with PN EN 15632-1-3 norm and, due to its innovative design it has a AT-15-8842/2012 Technical Institute Approval of Construction Technology

* In a projected temp. of 95° C 10 bar for hot water we use PEX SDR 7,4

Pipeline construction is based on the Patent 189276 and includes an air space between the pipe insulation and the enclosure insulation to form an additional thermal barrier and is sealed with a thermal plug. Such a design also provides exceptional flexibility of the pipeline. Thermal for self-assembly in a set with pipeline in amount suitable for sections

External housing m / m	250	250	250	250	200	200	160	160
PE-X pipe external / m DZ	2x75	2x63	2x50	2x50	2x50	2x40	2x32	2x25
	1x40	1x40	1x50	1x40	1x32	1x32	1x25	1x20
Inner diameter / m	1x25	1x25	1x32	1x25	1x20	1x20	1x20	1x16
	2x65	2x51,4	2x40,8	2x40,8	2x40,8	2x32,6	2x26	2x20,4
Bending radius mb	1x32,6	1x32,6	1x40,8	1x32,6	1x26	1x26	1x20,4	1x16
	1x20,4	1x20,4	1x26	1x20,4	1x16	1x16	1x16	1x12
Maximum running length	1,2	1,2	1,2	1,2	0,9	0,8	0,6	0,6
Catalog No.	100	100	100	100	100	100	100	100
Net price EURO for 1 meter	400250275	400250263	400250250	400250251	400200250	400200240	400160232	400160225
	126,00	109,00	103,00	101,00	91,00	79,00	61,00	52,00



Pipe Black Corrugated HDPE 450N, PESZEL

Mark Ø Dz x d [mm]	Standard length [m]	Trade Unit	Catalog number	Net price USD/m
63	scroll 50	1m	P450063050	0,93
75	scroll 50	1m	P450A75050	1,12
90	scroll 50	1m	P450A90050	1,16
110	scroll 50	1m	P450A11050	1,63
125	scroll 50	1m	P450012550	1,74
160	scroll 50	1m	P450016050	3,02

Other diameter sets and series: 3 transmission pipes, five, seven; PE pipes with a heating cable we make to order. Please submit queries. All net prices, plus VAT 23%



Single Syncopex® pipe PE SDR 11, Cold water

Pipeline designed for water supply and industrial networks. Blue or black conductor tube PE-100 SDR 11 PN 16 PN-EN 12201-2-2011. Thermal insulation made of closed cell foamed PEX, resistant to ageing.

Pipeline with pre-insulation manufactured in accordance with PN EN 15632-1-3 norm.

Outer casing m/m	250	200	200	200	160
Outer pipe PEX m/m DZ	160x14,6	140x12,7	125x11,4	110x10,0	90x8,2
Bending radius m	-	-	-	0,80	0,70
Maximum length	12 m	12 m	12 m	100 m	100 m
Catalog No.	111224160	111224140	111200125	111200110	111200090
Net price EURO for 1 meter	91,00	77,00	60,00	55,00	44,00

Outer casing m/m	160	140	125	125	110	90	90
Outer pipe PEX m/m DZ	75x6,8	63x5,8	63x5,8	50x4,6	40x3,7	32x3,0	25x2,3
Bending radius m	0,70	0,55	0,50	0,45	0,35	0,25	0,25
Maximum length	100	100	100	100	100	100	100
Catalog No.	111160075	111160063	111125060	111125050	111110040	111090032	111090025
Net price EURO for 1 meter	38,00	33,00	29,00	27,00	23,00	18,00	17,00



Single Syncopex® PE pipe SDR 17, Cold water

Pipeline for cold drinking water, cooling systems, heat pumps, geothermal installations. Transmission pipe PE-100 SDR 17 polyethylene 12201-2-2011

Thermal insulation made of closed cell foamed PEX, resistant to ageing. Insulated pipeline is manufactured in accordance with PN EN 15632-1-3 norm.

Outer casing m/m	250	200	200	200	160
Outer pipe PEX m/m DZ	160x9,5	140x8,3	125x7,5	110x6,6	90x5,4
Bending radius m	-	-	-	0,80	0,70
Maximum length	12 m	12 m	12 m	100 m	100 m
Catalog No.	117224160	117224140	117200125	117200110	117200090
Net price EURO for 1 meter	81,00	74,00	52,00	44,00	39,00

Outer casing m/m	160	140	125	125	110	90
Outer pipe PEX m/m DZ	75x4,5	63x3,8	63x3,8	50x3,8	40x2,4	32x2,0
Bending radius m	0,70	0,55	0,50	0,45	0,35	0,25
Maximum length	100	100	100	100	100	100
Catalog No.	117160075	117160063	117125063	117125050	117110040	117090032
Net price EURO for 1 meter	34,00	30,00	27,00	27,00	22,00	16,00



Single pipe SYNCOPEX® GEO PE, SDR 17

Pipeline for cold drinking water, cooling systems, heat pumps, geothermal installations. Transmission pipe PE-100 SDR 17 polyethylene 12201-2-2011

Thermal insulation made of closed cell foamed PEX, resistant to ageing. Insulated pipeline is manufactured in accordance with PN EN 15632-1-3 norm.

Outer casing m/m	90	75	63	63
Outer pipe PEX m/m DZ	63x3,8	50x3,8	40x2,4	32x2,0
Bending radius m	0,30	0,30	0,25	0,20
Maximum length	100	100	100	100
Catalog No.	117190063	117190050	117163040	117163032
Net price EURO for 1 meter	14,00	14,00	11,00	11,00

* PE pipelines on request are manufactured with a frost protection cable with a built-in one thermostat or mounted separately. Please send your inquiries.

INSTALLATION PIPES SYNCOPEX®

Pipe system for interior and industrial installations

Syncopex pipelines are manufactured in the diameter range from DZ 16 mm to DZ 450 mm made of cross-linked polyethylene, obtained as a result of the Engel modification method. SYNCOPEX® pipes have an EVOX anti-diffusion barrier, protecting against penetration of oxygen into the heating medium. They are used to perform local distribution, underfloor heating and risers installation in central heating in multi family housing. SaniPEX pipes are used most often for local distribution and installation risers of cold and hot water in construction of single and multifamily housing.

They must not be used in heating installations, due to the lack of EVOH anti-diffusion barrier.

The multi-layered system of pipes Pert-Al-Pert is available in the range of diameters from Dz 16 mm to Dz 32 mm. Wide universality of these pipes allows the use of one type of pipe for mounting of central heating, underfloor heating and wall heating, as well as, hot and cold tap water. The pipes are characterized by high resistance to pressure and temperature, durability, minimal linear expansion, low weight, high plasticity and resistance.



Pipe, PN6/95°C with EVOH diffusion barrier heating medium distribution in central heating installations Distribution of heating medium in central heating installations

Material: PEX-a / Series: SDR 11

Mark Ø Dz x d [mm]	Standard length [m]	Trade Unit	Catalog number	Net price EURO/m
16 x 2,0	scroll 200	200	516 200 016	1,26
	scroll 500	500	516 500 016	1,26
20 x 2,0	scroll 120	120	516 120 020	1,45
	scroll 480	480	516 480 020	1,45
25 x 2,3	scroll 100	100	516 100 025	2,20
	scroll 2000	2000	516 200 025	2,20
32 x 2,9	scroll 100	100	516 100 032	3,50
	scroll 2000	2000	516 200 032	3,50
40 x 3,7	scroll 100	100	516 100 040	5,44
	scroll 1500	2000	516 200 040	5,44
50 x 4,6	scroll 100	100	516 100 050	7,73
	scroll 1000	1000	516 001 050	7,73
63 x 5,8	scroll 100	100	516 100 063	12,61
	scroll 600	500	516 500 063	12,61
75 x 6,8	scroll 100	100	516 100 075	17,98
	scroll 500	500	516 500 075	17,98
90 x 8,2	scroll 100	100	516 100 090	24,72
	scroll 300	300	516 300 090	24,72
110 x 10,0	scroll 100	100	516 100 110	146,58
	scroll 200	200	516 200 110	146,58
125 x 11,4	scroll 100	100	516 100 125	46,98
160 x 14,6	scroll 60	60	516 060 160 ₁₎	78,14
200 x 18,1	12	12	516 012 200 ₂₎	-
225 x 20,4	12	12	516 012 225 ₂₎	-
250 x 22,7	12	12	516 012 250 ₂₎	-
280 x 25,4	12	12	516 012 280 ₂₎	-
315 x 28,6	12	12	516 012 315 ₂₎	-
355 x 32,2	12	12	516 012 355 ₂₎	-
450 x 50,0	12	12	516 012 450 ₂₎	-

1) pozycja dostępna na zamówienie

2) cena i termin realizacji określane na zapytanie ofertowe

Pipe for floor heating, PN6/95°C with EVOH diffusion barrier

Material: PEX-a / Series: SDR 11

Mark Ø Dz x d [mm]	Standard length [m]	Trade Unit	Catalog number	Net price EURO/m
16 x 2,0	scroll 200	200	516 200 016	1,16
	scroll 500	500	516 500 016	1,16
20 x 2,0	scroll 120	120	516 120 020	1,28
	scroll 480	480	516 480 020	1,28

PIPE saniPEX, PN6/95°C for the transfer of hot or cold potable water

Material: PEX-a / Series: SDR 7,4

Mark Ø Dz x d [mm]	Standard length [m]	Trade Unit	Catalog number	Net price EURO/m
16 x 2,2	scroll 100	100	510 100 016	1,21
20 x 2,8	scroll 50	120	510 050 020	1,69
	scroll 100	480	510 100 020	1,69
25 x 3,5	scroll 50	100	510 050 025	2,71
	scroll 100	2000	510 100 025	2,71
32 x 4,4	scroll 100	100	510 100 032	4,66
40 x 5,5	scroll 100	100	510 100 040	7,79
50 x 6,9	scroll 100	100	510 100 050	12,70
63 x 8,6	scroll 100	100	510 100 063	17,95
75 x 10,3	scroll 100	100	510 100 075	26,51
90 x 12,3	scroll 100	100	510 100 090	32,11
110 x 15,1	scroll 100	100	510 100 110	41,68
125 x 17,1	scroll 100	100	510 012 125 ₁₎	-
160 x 21,9	scroll 60	60	510 012 160 ₁₎	-
200 x 27,3	12	12	510 012 200 ₁₎	-
225 x 30,8	12	12	510 01 225 ₁₎	-

PIPE / AL / PERT

Mark Ø Dz x d [mm]	Standard length [m]	Trade Unit	Catalog number	Net price EURO/m
16 x 2,0	scroll 200	200	416 200 016	1,05
20 x 2,0	scroll 100	100	416 100 020	1,63
26 x 3,0	scroll 100	100	416 100 026	3,19
32 x 3,0	scroll 50	50	416 050 032	5,23

Zewnętrzna średnica rury D [mm]	Ø 16	Ø 20	Ø 26	Ø 32
Grubość ścianki (mm)	2,0	2,0	3,0	3,0
Grubość aluminium (mm)	0,2	0,25	0,3	0,4
Waga (kg/m)	0,105	0,14	0,27	0,347
Pojemność wodna (l/m)	0,113	0,201	0,314	0,531
Max. temperatura (°C)	95	95	95	95
Max. ciśnienie dla 95°C (bar)	10	10	10	10
Min. promień gięcia	5D	5D	5D	5D

Pipe PE 100 SDR, PN10, Cold water

Mark Ø Dz x d [mm]	Standard length [m]	Trade Unit	Catalog number	Net price EURO/m
32x2,0	100	1m	170032100	0,63
40x2,4	100	1m	170040100	0,93
50x3,8	100	1m	170050100	1,40
63x3,8	100	1m	170063100	2,33
75x4,5	100	1m	170075100	3,26
90x5,4	100 L=50	1m	170090100	4,65
110x6,6	L=50	1m	170110100	6,98
125x7,5	L=12	1m	170125100	8,84
160x8,3	L=12	1m	170160100	14,65
200x11,9	L=12	1m	170200100	22,33
250x14,8	L=12	1m	170250100	34,19
315x18,7	L=12	1m	170315100	53,49

HELA - H Screwing, PN6



16-32 m/m



40-160 m/m

The fittings are made of brass resistant to dezincification in accordance with PN-EN 1254-3/4 norm, thread according to ISO7

No. of product	Outer diameter GZ of transmission pipe m/m	Thickness of the pipe PEX m/m	Outer thread GZ inches	Net price EURO/pcs
606016001	16	2,0	3/4	7,91
606020001	20	2,0	3/4	10,59
606025001	25	2,3	1	11,04
606032001	32	2,9	1	11,75
606040114	40	3,7	1.1/4	26,57
606050114	50	4,6	1.1/4	31,78
606063002	63	5,8	2	50,30
606075002	75	6,8	2.1/2	84,51
606090003	90	8,2	3	119,36
606110004	110	10	4	163,59
606125005	125	11,4	4	509,10

HELA - S, PN6 Jointing Equal



The fittings are made of brass resistant to dezincification in accordance with PN-EN 1254-3/4, threads in accordance with ISO7

No. of product	Outer diameter GZ of transmission pipe m/m	Outer thread GZ inches	Net price EURO/pcs
626025001	25	2,3	23,88
626032114	32	2,9	37,60
626040114	40	3,7	50,75
626050114	50	4,6	63,28
626063002	63	5,8	99,43
626075002	75	6,8	149,37
626090003	90	8,2	243,86
626110004	110	10	313,97
626125005	125	11,4	594,41

All net prices, plus VAT 23%



HELA - T-piece

No. of product	Outer diameter GZ of transmission pipe m/m	Outer thread GZ inches	Net price EURO/pcs
611020001	3x20	3/4	4,74
611025001	3x25	1	6,47
611032114	3x32	1.1/4	10,80
611050002	3x50	2	26,44
611065003	3x65	2.1/2	105,24
611080003	3x80	3	107,77
611100004	3x100	4	196,81
611125005	3x125	5	294,16

HELA muff - M



Nr art.	Gwint zewn. GZ m/m	Gwint zewn. GZ cale	Net price EURO/pcs
618020020	20	3/4	2,81
618025025	25	1	3,84
618032032	32	1.1/4	5,47
618050050	50	2	17,42
618065065	65	2.1/2	57,47
618080080	80	3	54,56
618100100	100	4	85,25

HELA elbow - V, 90 °



No. of product	Outer diameter GZ of transmission pipe m/m	Outer thread GZ inches	Net price EURO/pcs
612020001	20	3/4	3,88
612025001	25	1	4,85
612032114	32	1.1/4	13,22
612050002	50	2	20,84
612065003	65	2.1/2	65,36
612080003	80	3	84,30
612100004	100	4	120,66
612125005	125	5	253,00



HEL A - D nipple with external thread

No. of product	Outer diameter GZ of transmission pipe m/m	Outer thread GZ inches	Net price EURO/pcs
614020020	20x20	3/4x3/4	1,97
614025020	25x20	1x3,4	3,95
614025025	25x25	1x1	3,43
614032025	32x1	1.1/4x1	5,95
614032032	32x32	1.1/4x1.1/4	4,33
614050032	50x32	2x1.1/4	17,48
614050050	50x50	2x2	9,04
614080050	80x50	3x2	62,09
614080080	80x80	3x3	42,27
614100080	100x80	4x3	129,93
614100100	100x100	4x4	97,39

HEL A - B, Reducer



No. of product	Outer diameter GZ of transmission pipe m/m	Outer thread GZ inches	Net price EURO/pcs
613025020	25x20	1x3/4	2,70
613032025	32x25	1.1/4x1	4,71
613050025	50x25	2x1	11,98
613050032	50x32	2x1.1/4	11,98
613065050	65x50	2.1/2x2	28,47
613080050	80x50	3x2	44,15
613080065	80x65	3x2.1/2	57,57
613100050	100x50	4x2	134,26
613100080	100x80	4x3	107,40
613125080	125x80	5x3	160,95
613125100	125x100	5x4	161,47



HEL A flange - F

No. of product	Outer diameter GZ of transmission pipe m/m	Outer thread GZ inches	Net price EURO/pcs
619000025	25	1	42,52
619000032	32	1.1/4	52,90
619000050	50	2	63,87
619000080	80	3	87,24
619000100	100	4	111,93



25 mm



32-160 mm

HEL A Coupling transitional for welding, PN 6

No. of product	Outer diameter GZ of transmission pipe m/m	Outer thread GZ inches	Net price EURO/pcs
706025001	25	26,9	40,68
706032001	32	33,7	45,21
706042001	40	42,4	58,75
706048001	50	48,3	64,19
706060001	63	60,3	78,10
706076001	75	76,1	141,28
706089001	90	88,9	179,88
706114001	110	114,3	273,93
706139001	125	139,7	475,53

For sealing T-joints, sleeves, knees and flanges of type HELA should use threads, Teflon tapes or similar sealing materials

House entrance



Composition tightly sealed with a heat shrink sleeve from the ground. Composition SN 8 shrink tube heat shrink sleeve

Product No.	Outer diameter DZ of pipe pre-insulated m/m	Outer diameter GZ of pipe protective m/m	Minimum length m/m	Net price EURO/pcs
810101180	90-110	160	500	44,00
810125180	125	160	500	44,00
810140180	140	250	500	56,00
810160220	160	250	500	56,00
810200260	200	315	500	65,00
810250300	250	350	500	74,00

T- insulation set



Product No.	Outer diameter DZ of pipe pre-insulated m/m	Outer diameter GZ of pipe protective m/m	Minimum length m/m	Net price EURO/pcs
811110180	90-110	180	650	199
811125180	125	180	650	199
811140180	140	180	650	199
811160200	160	225	850	207
811200250	200	225	850	212
811250280	250	280	850	278

Elbow insulation set



Product No.	Outer diameter DZ of pipe pre-insulated m/m	Outer diameter GZ of pipe protective m/m	Minimum length m/m	Net price EURO/pcs
814110180	90-110	180	450	142,00
814125180	125	180	450	142,00
814140180	140	180	450	142,00
814160200	160	225	500	165,00
814200250	200	225	500	165,00
814250280	250	280	500	219,00



Straight insulation set

Insulating: sleeve, shring sleeve

Product No.	Outer diameter DZ of pipe pre-insulated m/m	Outer diameter GZ of pipe protective m/m	Minimum length m/m	Net price EURO/pcs
812110180	90-110	180	550	112,00
812125180	125	180	550	112,00
812140180	140	180	550	112,00
813160200	160	225	650	130,00
813200250	200	225	650	130,00
813250280	250	280	650	158,00

Caps - shrink caps



Product No.	For pipe PEX m/m	Outer diameter. Pre-insulated pipe. m/m	Net price EURO/pcs
910011050	25-50	90-110	15,00
910012550	40-50	125	18,00
910014075	50-75	140	21,00
910016090	63-90	160	24,00
910200110	90-110	200	27,00
910200125	125	200	32,00
910250160	140-160	250	42,00



Product No.	For pipe PEX m/m	Outer diameter. Pre-insulated pipe. m/m	Net price EURO/pcs
911214024	2x25 - 40	140	26,00
911216024	2x32-40	160	29,00
911220025	2x50	200	29,00
911222475	2x63(2x75)	250	42,00
912140032	40+20	140	26,00
912160050	50+20	160	29,00
912200063	63+32	200	29,00
912250075	75+40 (50)	250	42,00



Caps - interference plugs for a single pipeline

Product No.	For pipe PEX m/m	Outer diameter. Pre-insulated pipe. m/m	Net price EURO/pcs
920009025	25	90	18,00
920009032	32	90	18,00
920011040	40	110	18,00
920011050	50	125	20,00
920014063	63	140	20,00
920016075	75	160	20,00
920020075	75	200	23,00
920016075	90	160	20,00
920020090	90	200	23,00
920200110	110	200	23,00
920200125	125	200	23,00

Caps - interference plugs for double pipelines

Product No.	For pipe PEX m/m	Outer diameter. Pre-insulated pipe. m/m	Net price EURO/pcs
921140225	2x25	140	20,00
921140232	2x32	140	20,00
921160240	2x40	160	20,00
921160232	2x32	160	20,00
921200240	2x40	200	23,00
921200250	2x50	200	23,00
921250263	2x63	250	37,00
921250275	2x75	250	37,00
922140201	20+16	140	20,00
922140252	25+20	140	20,00
922140322	32+20	140	20,00
922140402	40+25	140	20,00
922160403	40+32	160	20,00
922160502	50+25	160	20,00
922200633	63+32	200	23,00
922224634	63+40	250	23,00
922250635	75+50	250	37,00
922250636	90+50	250	41,00



Caps - interference plugs for multi-pipe pipelines

Product No.	For pipe PEX m/m	Outer diameter. Pre-insulated pipe. m/m	Net price EURO/pcs
924160252	2x25 1x20 1x16	160	23,00
924160323	2x32 1x25 1x20	160	23,00
924200240	2x40 1x25 1x20	200	28,00
924200250	2x50 1x32 1x20	200	28,00
924250250	2x50 1x40 1x25	250	42,00
924250251	2x50 1x40 1x32	250	42,00
924250263	2x63 1x40 1x25	250	42,00
924250264	2x75 1x40 1x25	250	42,00

Warning tape with metal insert

Nr art.	Roll width cm	Roll length m	Net price EURO/pcs
930100100	10	100	1,00



Repair tape - shrink

Nr art.	Width rolls cm	Thickness mm tapes	Thickness glue mm	Net price EURO/pcs
940150015	150	1	0,1	9,00



Producent of the system:



Multi-business company

86-061
Niwy, st. Karpacka, 1A

tel. **52 346 31 20**
tel./fax **52 344 12 39**

www.synco.pl